



INVESTOR IN PEOPLE

GBO4/4342

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 17 NOV 2004

WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

He Behen


Dated

3 November 2004

**PRIORITY
DOCUMENT**


SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

BEST AVAILABLE COPY



Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference
P104180GB

2. Patent application number
(The Patent Office will fill in this part)

0327109.5

21 NOV. 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

ARCHITECTURAL PRODUCTS + COMPONENTS
Factory Building 1
East of High-tech Road 9,
Qiaonan

Patents ADP number (if you know it)

Area of Xiaoshan Economic & Technological
Development Zone Hangzhou

If the applicant is a corporate body, give the country/state of its incorporation

Zhejiang Province, CHINA.

CHINA 8758005001

4. Title of the invention

A MORTICE LOCK

5. Name of your agent (if you have one)

HARRISON GODDARD FOOTE

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Orlando House
11c Compstall Road
Marple Bridge
Stockport
SK6 5HH - GB

Patents ADP number (if you know it)

14571002

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	0
Description	9
Claim(s)	0
Abstract	0
Drawing(s)	7

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

Harrison Goddard Foste

20/11/2003

12. Name and daytime telephone number of person to contact in the United Kingdom
- MIKE AJELLO 0161 427 7005

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

A MORTICE LOCK

THIS INVENTION concerns mortice locks of the type including a deadbolt which is retained within a lock case and movable between an unlocking position wherein the deadbolt is disposed within the lock case, and a locking position in which it extends outwardly from a fore-end thereof.

The invention is particularly concerned with providing a mortice lock of this kind wherein the "throw" of the deadbolt from the front or fore-end of the casing is as much as 20mm within a standard lock case of 63.5mm (nominal).

Conventionally, it has not been possible to construct a lock of this size with a 20mm bolt throw using a mechanism which both extends and retracts the deadbolt in a positive manner and prevents the bolt from being pushed back manually from its outermost locking position.

In locks of this kind there is usually provided a rotary driving mechanism which may be a key, a key cam or a cylinder cam which makes contact with the deadbolt to extend and retract it during rotation of the driving mechanism. In order to ensure the maximum throw of the bolt head the driving mechanism should


maintain contact with the deadbolt throughout its movement, yet allow the bolt to pass over the axis of rotation of the driving mechanism when the bolt is retracted.

According to the present invention there is provided a mortice lock including a deadbolt retained within a lock case and movable between an unlocking position wherein the deadbolt is disposed within the lock case, and a locking position in which it extends outwardly from a fore-end thereof, and a driving mechanism rotatable about an axis transverse to the direction of movement of the deadbolt and having a cam which connects with and moves the deadbolt between said positions; characterised by at least one contact member mounted on and movable with respect to the deadbolt between a first position in which the contact member maintains contact with the driving member to effect a full throw of the deadbolt in one direction, and a second position to enable a full throw of the deadbolt in an opposite direction.

The driving member may be a key.

The driving member may be cylinder cam.

The driving member may be a key cam associated with multiple levers.



Two contact members may be mounted on the deadbolt one of which maintains contact with the driving member throughout movement of the deadbolt into the locking position, the other maintaining contact with the driving member throughout movement of the deadbolt into the unlocking position.

Each contact member may be movable into a position in which it prevents movement of the deadbolt.

The or each contact member may have a cam follower residing in a track in the lock case, the track being formed to effect movement of the contact member between its first and second positions.

The deadbolt may, in its locking position, extend from the fore-end of the lock case by 20mm.

Embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings, in which:-


Fig. 1 is an exploded view of a mortice lock made in accordance with a first embodiment of the invention; and

Figs. 2 to 12 illustrate the lock of Fig. 1 assembled and showing progressive movement of the lock mechanism between an unlocking and a locking position of a deadbolt being part of the lock.

Referring now to Fig. 1, the mortice lock comprises a lock case 10, 11 having a for-end plate 12 with apertures 13 and 14 through which extend a latch 15 and a deadbolt 16 respectively.

Within the lock case 10, 11, in this example, is a cylinder lock 17 having a driving member in the form of a rotatable cam 18 which rotates about the axis of a barrel 19 which is turned by a key inserted into a slot 20.

A pair of contact members 21, 22 are slidably mounted on the deadbolt 16 having pins 23 and 24 respectively, which permit limited vertical movement within slots 25 and 26 respectively in the deadbolt 16. A dummy lever 27 moves horizontally within the lock case along with deadbolt 16 and has a pin (not shown) which rides



in a horizontal track 28 in the lock case 10. The pins 23 and 24 are also constrained to ride in a curved track 31 as will be described.

The latch 15 mounted on a latch pin 29 together with appropriate springs, is normally retained in a position extending outwardly from apertures 13 but is retracted within the casing during closure of a door in which the lock is inserted. The latch mechanism itself forms no part of the present invention, being of a standard design.

A spring 30 urges the sliding contact members 21 and 22 in a downwards direction in relation to deadbolt 16 during operation of the lock.

Referring now to Fig. 2, it will be seen that the dead lock 16 is in its unlocking position wholly contained within the lock casing 10, 11 but with its forward end substantially flush with the front of the fore-end plate 12. In this position the cam 18 is in a fully unlocking position and is in contact with a lower region of the sliding contact member 22 which itself is in a lowermost position with respect to the deadbolt 16.


In this position, the other sliding contact member 21 is in its uppermost position with respect to the deadbolt 16 and is thus located overhead of the body of the cylinder cam 17.

Referring now to Fig. 3, as the cam 18 is rotated in an anti-clockwise direction in the drawing, it leaves contact with sliding contact member 22 then making contact with the lower region of the sliding contact member 21.

Referring now to Fig. 4 with continued rotational movement of the cam 18 it pushes the sliding contact member 21 towards the left hand side of Fig. 3 thus starting to advance the deadbolt 16 from the casing. Thus, the pin 24 of sliding contact member 22 commences its travel upwardly in the track 31 whereby the member 22 starts to rise.

Fig. 5 shows the sliding contact member 22 in a further elevated position while cam 18 continues to push against sliding contact member 21 to advance the deadbolt 16 further from the casing.

Referring now to Fig. 6 it will be seen that the sliding contact member 22 has reached its maximum height with the pin 24 at the highest point of the track 31, and in this position the sliding



contact member 21 is starting to descend constrained by the track 31 while the bolt 16 continues to advance from the casing.

Fig. 7 shows the position of maximum extension of the deadbolt 16. This extension is 20mm in the present example as required by the design of this mortice lock in a standard 63.5mm casing. The extended throw to 20mm is provided by continuous contact between the cam 18 and the then-lowered sliding contact member 21. It will be seen also that in this position the sliding contact member 22 is at its maximum height and has therefore been permitted to ride over the top of the cylinder cam 17.

Contact of the cam 18 with the bottom of the sliding contact member 21 prevents the deadbolt 16 from being pushed back into the casing so that the 20mm throw is maintained.


Referring now to Fig. 8, it will be seen that if the cam 18 is allowed to rotate even further in an anti-clockwise direction thus to move out of contact with the sliding contact member 21, nevertheless, the bolt cannot be pushed back very far because the sliding contact member 21 would then come into contact with the top of the body of the cylinder cam 17.

Referring now to Fig. 9, it will be seen that as the cam 18 is rotated in the clockwise direction it comes into contact with the lower end of the sliding contact member 22 to commence retracting of the deadbolt 16.

Fig. 10 shows a continuation of this movement whereupon the sliding contact member 21 rises to a point where, in Fig. 11, it may pass over the top of the body of the cylinder cam 17. Also in that position, the sliding contact member 22 is beginning to descend towards its lowermost position, and in Fig. 12 it is shown in that position such that the cam 18 will continue to push back the bolt 16 into its fully retracted position once again as shown in Fig. 12. Thus the parts are returned to their respective positions as illustrated in Fig. 2.

The spring 30 which locates over a pin 32 in the casing 10 bears against the upper edge of dummy lever 27 to urge the sliding contact members 21 and 22 into their lowermost positions. However, the sliding members are permitted to rise by pushing against the spring 30 when constrained by the track 31.

It will be appreciated that a mortice lock made in accordance with the invention ensures a maximum bolt throw by maintaining a connection between the driving mechanism and the



bolt for a maximum extent of rotation of the driving mechanism, while allowing the bolt, or parts connected thereto, to rise and thus pass over the body of the driving mechanism. The arrangement further provides that the bolt cannot be pushed back when in any of its positions of extension from the lock case.

The cylinder cam 17 may be replaced by a multiple lever assembly as required for three, five or seven lever locks which provide additional security. In such an arrangement, the cam 18 is replaced by a key cam which receives the forward end of the key and is rotated by it.

In a simplified embodiment a key itself may advance and retract the deadbolt by direct contact with the sliding contact members 21 and 22.

The contact members may be rotatably or otherwise movable with respect to the bolt 16 thus to extend the range of contact between the cam 18 and the bolt 16, to provide the extended bolt throw in accordance with the invention.

The contoured track 31 in the casing may be replaced by wedges or other abutment means mounted in the casing and contacted by the contact members.




Fig. 1




FIG. 2




FIG. 3




FIG. 5




FIG. 4





FIG. 6



Throw distance=20mm

FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 13





FIG. 12

PCT/GB2004/004342



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.